



PC2230WG



Product Description

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

Brand: flexBOX®

Catalog #: PC2230WG

Width: 3-1/2 in.

Depth: 2-13/16 in.

Volume: 21.5 cu. in.

Type of Installation: Old Work
Round Ceiling Box

Carton Quantity: 24

Carton Weight: 9 lb.

UPC: 085339980292

UNSPSC: 39121316

Patents:

U.S. Patent No. 6,365,831 B1

Country of Origin: United States of America

FEATURES

Machine tapped fixture holes, round exterior for easy cut-in, ground strap

APPLICATION

Old work residential construction 2 HR fire resistive walls. Meets requirements of Articles 314.27 (A1) and 314.27 (D) of the 2014 NEC. Suitable for use in mounting utilization equipment (wall sconce lights, alarm system strobe/speaker, smoke detector and low-profile LED lighting) weighing six pounds or less.

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Black

ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

MATERIAL

Polycarbonate

Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw

MOUNTING

Snap bracket/box flange wall compression

SUPPORT RATING

Meets NEC for wall applications