PJ-20N



Product Description

4 square inch electrical junction box for use with nonmetallic sheathed cable

Brand: flexBOX®
Catalog #: PJ-20N

Height: 4 in. Width: 4 in. Depth: 1-5/8 in. Volume: 20.5 cu. in.

Type of Installation: New Work

Wall Box

Carton Quantity: 48 Carton Weight: 11 lb.

UPC: 085339990017 **UNSPSC:** 39121332

Patents:

U.S. Patent No. 6,365,831 B1

Country of Origin: United States of America

FEATURES

Machine tapped cover screw holes, cover screws included

APPLICATION

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications - 2 HR fire resistive walls

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Black

MATERIAL

Polyvinyl Chloride

MOUNTING

Angled mid-nails

ADDITIONAL MATERIALS

Carbon steel fasteners

Plated carbon steel fasteners